

GOVERNMENT MEDICAL COLLEGE KOLLAM

PARIPPALLY, KERALA – 691574 INDIA Phone: 0474-2572574 e-mail: gmckollam@gmail.com

No. C1/9421/2023/GMC-KLM

Dated: 15/12/2023

QUOTATION NOTICE

Quotation Number	C1/9421/2023/GMC-KLM Dated- 15.12.2023			
Due date and time for receipt of quotations	At 2.30 pm on: 05/01/2024			
Date and time for opening of quotations	At 3.00 pm on : 05/01/2024			
Date up to which the rates are to remain firm for acceptance	31-03-2024			
Designation and address of officer to whom the quotation is to be addressed	Principal Govt. Medical College, Kollam -691 574			

Superscription: Purchase of Finger Pulse Oxymeter, Digital Thermometer, Sphygmomanometer, Aneroid Sphygmomanometer & Glucometer

(Department of Casualty)

(Specification are in Annexure I) * Rate should be quoted in the following format

Sl. No	Item Name	Unite Unit cost Pack excluding Size GST		% of GST	Unit cost including	Qty.	Total cost
			& Rate	GST	Qty.	Including GST	
	and the second second						

Sealed quotations are invited for the supply of the materials specified in the schedule attached below/overleaf. The rates quoted should be for delivery of the articles at the place mentioned below the schedule. The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted above. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for delivery of the articles should also be mentioned. Quotations not stipulating period of firmness and with price variation clause and/or 'subject to prior sale' condition are liable to be rejected.

The acceptance of the quotations will be subject to the following conditions:


- Acceptance of the quotation constitutes a concluded contract. Nevertheless, the successful tenderer must within a fortnight/a month after the acceptance of his quotation furnish 5 per cent of the amount of the contract as security deposit and execute an agreement at his own cost for the satisfactory fulfillment of the contract, if so required.
- Withdrawal from the quotation after it is accepted or failure to supply within a specified time or according to specifications will entail cancellation of the order and purchases being made at the offerers expenses from elsewhere, any loss incurred thereby being payable by the defaulting party. In such an event the Government reserves also the right to remove the defaulter's name from the list of Government suppliers permanently or for a specified number of years.
- 3. Samples, duly listed, should be forwarded if called for under separate cover and the unapproved samples got back as early as possible by the offerers at their own expenses and the Government will in no case be liable for any expenses on account of the value of the samples or their transport

cnarges, etc. In case, the samples are sent by railway; the railway receipt should be sent separately, and not along with the quotation since the quotation will be opened only on the appointed day and demurrage will have to be paid if the railway parcels are not cleared in time. Quotations for the supply of materials are liable to be rejected unless samples, if called for of the materials tendered for are forwarded. The approved samples may or may not be returned at the discretion of the undersigned. Samples sent by V.P. Post or "freight to pay" will not be accepted.

- 4. No representation for enhancement of price once accepted will be considered during the currency of the contract.
- 5. Any attempt on the part of tenderers or their agents to influence the Officers concerned in their favour by personal canvassing will disqualify the tenderers.
- 6. If any license or permit is required, tenderers must specify in their quotation and also state the authority to whom application is to be made.
- 7. The quotation may be for the entire or part supplies. But the tenderers should be prepared to carry out such portion of the supplies included in their quotation as may be allotted to them.
- 8. (a) In cases where a successful tenderer, after having made partial supplies fails to fulfill the contracts in full, all or any of the materials not supplied may, at the discretion of the Purchasing Officer be purchased by means of another tender/quotation or by negotiation or from the next higher tenderer who had offered to supply already and the loss, if any, caused to the Government shall thereby together with such sums as may be fixed by the Government towards damages be recovered from the defaulting tenderer.
 - (b) Even in cases where no alternate purchases are arranged for the materials not supplied, the proportionate portion of the security deposit based on the cost of the materials not supplied at the rate shown in the tender of the defaulter shall be forfeited and balance alone shall be refunded.
 - (c) Any sum of money due and payable to the contractor (including Security Deposit returnable to him) under this contract may be appropriated by the Purchasing Officer or Government or any other person authorized by Government and set-off against any claim of the Purchasing Officer or Government for the payment of a sum of money arising out of or under any other contract made by the contractor with the Purchasing Officer or Government or any other person authorized by Government.
- 9. The prices quoted should be inclusive of all taxes, duties, cesses, etc., which are or may become payable by the contractor under existing or future laws or rules of the country of origin/supply or delivery during the course of execution of the contract.
- 10. (a) Ordinarily payments will be made only after the supplies are actually verified and taken to stock but in exceptional cases, payments against satisfactory shipping documents including certificates of Insurance will be made up to 90 per cent of the value of the materials at the discretion of Government. Bank charges incurred in connection with payment against documents through bank will be to the account of the contractor. The firms will produce stamped prereceipted invoices in all cases where payments (advance/final) for release of railway receipts/shipping documents are made through Banks. In exceptional cases where the stamped receipts of the firms are not received for the payments (in advance) the unstamped receipt of the Bank (i.e. counterfoils of pay-in-slips issued by the Bank) alone may be accepted as a valid poor for the payment made.
 - (b) The tenderers shall quote also the percentage of rebate (discount) offered by them in case the payment is made promptly within fifteen days/within one month of taking delivery of stores.
- 11. Any sum of money due and payable to the successful tenderer or contractor from Government shall be adjusted against any sum of money due to Government from him under any other contracts.
- 12. Special conditions, if any, printed on the quotation sheets of the tenderer or attached with the tender will not be applicable to the contract unless they are expressly accepted in writing by the purchases.

Copy to:

- 1. Notice Board, GMC KLM/GMCH KLM
- 2. Website , GMC KLM



Draft

Specifications

- 1. Display type: 2.8 mm OLED/LCD Display with 128 X 64 pixel Resolution.
- SPO2 : Measurement range 70-99% Accuracy: +/- 2% on the stage of 70-99%
- 3. IR sensor: Two beams of different wavelength (660 nm glow and 940 nm near infrared light)
- 3. PR: Measurement Range : 30 BPM 240 BPM
- 4. Power : Two AAA 1.5 v alkaline batteries.
- 5. Power consumption : Below 30 mA
- 6. Automatic power off: The product shuts off by itself when no finger in the product for 8 seconds.
- 7. Pulse Intensity: Bargraph Indicator
- 8. Dimensions : 58 mm x 36 mm x 33 mm
- 9. Declaration: EMC of the product comply with IEC60601-1-2 STANDARD
- 10. Low power consumption, continuously work for 40 hours.
- 11. Low voltage indicator
- 12. Small volume, light weight and convenient to carry.

B 15faulpon

CLINICAL THERMOMETER DIGITAL

erwe I to Q.N. No. C-9421 2023 Greekens BFd 12/2013

- 1. For oral, rectal and underarm temperature measurement
- 2. 3-digit, + degree celcius (degree fahrenheit) display in 0.1 degree increment.
- 3. Beeps when measurement is completed.

Draft

- 4. Measurement Accuracy : ±0.1 degree celcius (32.0 to 42.0 degree celcius); ±0.2 degree fahrenheit (89.6 to 107.6 degree fahrenheit)
- 5. Memory recalls last reading.
- 6. Auto off function: Approximately 30 minutes after use or 3 minutes when not been used.
- 7.1 Year Manufacturer Warranty from date of purchase.

Amexine - III, to Q. N. No. R. |9421/2015] Griekin. Dated. 12/2013

BP Apparatus (SPHYGMOMANOMETER)

- Should have a measuring range from 0 to 300 mmHg.
- Made of first grade quality virgin material.
- . Permanent graduation marking on the glass tube.
- Control valve for perfect pressure drop.

the main .

- Surface plating adapted to all exposed metal parts to prevent corrosion
- Should be provided with adult arm cuffs of size medium & large and paediatric cuff.
- The inflating rubber bag should be capable of withstanding an internal pressure of 450 mmHg without leaking.
- The inflating bulb should be soft and should not have any joints or ridges.
- The fastening arrangements of the cuff should be of hook and loop type (Velcro).
 The threading a log and loop type
- The threading and fastening arrangement of the cuff should show no sign of slip or failure when subjected to the maximum test conditions.
- The rubber tubes used should have an internal diameter of 3 ± 0.5 mm and the external diameter should not be less than 8mm.
- · All parts should be replaceable in case of breakage.

11.55

• The tubes should be fitted with male and female leur connectors.

PRINCIPAL

Annemere IV to Q.N.ND.C. (9421/2023) amekin. Ord 12/2023

BP APPARATUS - ANEROID/SPRING DIAL TYPE- STAND MODEL

- 1. Should be aneroid type,
- 2. Should have ISI mark.
- 3. Should have a measuring range from 0 to 300 mmHg,
- 4. Should be provided with adult arm cuffs of size medium & large and paediatric cuff.
- 5. The dial mano meter markings and graduations should be permanent and 6. Clearly visible and filled with pigments, with diameter of minimum diameter of 160 mm.
- 7. Body & Bazel Aluminium die casted (Powder coated), screw type bazel
- 8. Sensing- corrugated phosphorous bronze twin capsule bellows.
- 9. Movement mechanism Brass

10. Connection: brass, nickel plated for 3-4 mm rubber hose.

- 11.Dial Aluminium
- 12. Pointer White coated, thin & sharp made of phosphorous Bronze
- 13. Window lenses Clear plastic.
- 14.All plastic parts, if any used should not crack, flake, peel or disintegrate in normal use.
- 15. The inflating rubber bag should be capable of withstanding an internal pressure of 450 mmHg without leaking.
- 16. The inflating bulb should be soft and should not have any joints or ridges.
- 17. The fastening afrangements of the cuff should be of hook and loop type (Velcro)
- 18. The threading and fastening arrangement of the cuff should show no sign of slip or failure when subjected to the maximum test conditions.
- 19. The rubber tubes used should have an internal diameter of 3 ± 0.5 mm and the external diameter should not be less than 8mm.

20.All parts should be replaceable in case of breakage.

21. The tubes should be fitted with male and female leur connectors.

22. Should be mounted on good quality wheels.

23. The stand body shall be made of mild steel and powder coated.

24. Warranty-minimum of one year

25.All fine specifications should be supported by manual or brochure.

PRINCIPAL

Annenwrer to Q.N.No. alguze/2005/gmckm

Dan

GLUCOMETER

- Enzyme
- Measurement Range
- Minimum Sample Size
- Result Calibration
- Battery Life
- Memory Up to
- Display Size
- Alternate Site Testing
- Test Time

:Glucose Oxidase : 20-600 mg/dL :1 μL :Plasma-equivalent : 1,000 tests or more :300 records with date and time : 35 mm x 32.5 mm or more :Fingertip, forearm, or palm : below 10 seconds

- Automatic Shutoff 2 minutes after last action or 5 sec after strip removal
- Large LCD display with bold numbers
- Branded/Star rated /CE certified equipment is essential for trouble free and accurate working.

