



GOVERNMENT MEDICAL COLLEGE

PARIPALLY, KOLLAM-691574

Telephone Office : 0474 2572574, Fax: 0474 2572579

Telephone Principal: 0474-2572572 Electronic mail: gmckollam@gmail.com

Section Email: acts.gmckollam@gmail.com

No. C2/8980/2022/GMC KLM

Dated:23/12/2022

QUOTATION NOTICE

Quotation Number	C2/8980/2022/GMC KLM Dated:23-12-2022
Due date and time for receipt of quotations	At 2.30 pm on 05/01/2023
Date and time for opening of quotations	At 3.00 pm on 05/01/2023
Date up to which the rates are to remain firm for acceptance	31-03-2023-Community Medicine
Designation and address of officer to whom the quotation is to be addressed	Principal Govt. Medical College, Kollam -691 574

Superscription: **Minor Instruments & Equipments**

* Rate should be quoted in the following format *(List Attached)*


Sl. No	Item Name	Unit Pack Size	Unit cost excluding GST	% of GST & Rate	Unit cost including GST	Qty	Total cost including GST

Sealed quotations are invited for the supply of the materials specified in the schedule attached below/overleaf. The rates quoted should be for delivery of the articles at the place mentioned below the schedule. The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted above. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for delivery of the articles should also be mentioned. Quotations not stipulating period of firmness and with price variation clause and/or 'subject to prior sale' condition are liable to be rejected.

The acceptance of the quotations will be subject to the following conditions:

1. Acceptance of the quotation constitutes a concluded contract. Nevertheless, the successful tenderer must within a fortnight/a month after the acceptance of his quotation furnish 5 per cent of the amount of the contract as security deposit and execute an agreement at his own cost for the satisfactory fulfillment of the contract, if so required.
2. Withdrawal from the quotation after it is accepted or failure to supply within a specified time or according to specifications will entail cancellation of the order and purchases being made at the offerers expenses from elsewhere, any loss incurred thereby being payable by the defaulting party. In such an event the Government reserves also the right to remove the defaulter's name from the list of Government suppliers permanently or for a specified number of years.
3. Samples, duly listed, should be forwarded if called for under separate cover and the unapproved samples got back as early as possible by the offerers at their own expenses and the Government will in no case be liable for any expenses on account of the value of the samples or their transport charges, etc. In case, the samples are sent by railway: the railway receipt should be sent separately, and not along with the quotation since the quotation will be opened only on the appointed day

- and demurrage will have to be paid if the railway parcels are not cleared in time. Quotations for the supply of materials are liable to be rejected unless samples, if called for of the materials tendered for are forwarded. The approved samples may or may not be returned at the discretion of the undersigned. Samples sent by V.P. Post or "freight to pay" will not be accepted.
4. No representation for enhancement of price once accepted will be considered during the currency of the contract.
 5. Any attempt on the part of tenderers or their agents to influence the Officers concerned in their favour by personal canvassing will disqualify the tenderers.
 6. If any license or permit is required, tenderers must specify in their quotation and also state the authority to whom application is to be made.
 7. The quotation may be for the entire or part supplies. But the tenderers should be prepared to carry out such portion of the supplies included in their quotation as may be allotted to them.
 8. (a) In cases where a successful tenderer, after having made partial supplies fails to fulfill the contracts in full, all or any of the materials not supplied may, at the discretion of the Purchasing Officer be purchased by means of another tender/quotation or by negotiation or from the next higher tenderer who had offered to supply already and the loss, if any, caused to the Government shall thereby together with such sums as may be fixed by the Government towards damages be recovered from the defaulting tenderer.
(b) Even in cases where no alternate purchases are arranged for the materials not supplied, the proportionate portion of the security deposit based on the cost of the materials not supplied at the rate shown in the tender of the defaulter shall be forfeited and balance alone shall be refunded.
(c) Any sum of money due and payable to the contractor (including Security Deposit returnable to him) under this contract may be appropriated by the Purchasing Officer or Government or any other person authorized by Government and set-off against any claim of the Purchasing Officer or Government for the payment of a sum of money arising out of or under any other contract made by the contractor with the Purchasing Officer or Government or any other person authorized by Government.
 9. The prices quoted should be inclusive of all taxes, duties, cesses, etc., which are or may become payable by the contractor under existing or future laws or rules of the country of origin/supply or delivery during the course of execution of the contract.
 10. (a) Ordinarily payments will be made only after the supplies are actually verified and taken to stock but in exceptional cases, payments against satisfactory shipping documents including certificates of Insurance will be made up to 90 per cent of the value of the materials at the discretion of Government. Bank charges incurred in connection with payment against documents through bank will be to the account of the contractor. The firms will produce stamped pre-receipted invoices in all cases where payments (advance/final) for release of railway receipts/shipping documents are made through Banks. In exceptional cases where the stamped receipts of the firms are not received for the payments (in advance) the unstamped receipt of the Bank (i.e. counterfoils of pay-in-slips issued by the Bank) alone may be accepted as a valid proof for the payment made.
(b) The tenderers shall quote also the percentage of rebate (discount) offered by them in case the payment is made promptly within fifteen days/within one month of taking delivery of stores.
 11. Any sum of money due and payable to the successful tenderer or contractor from Government shall be adjusted against any sum of money due to Government from him under any other contracts.
 12. Special conditions, if any, printed on the quotation sheets of the tenderer or attached with the tender will not be applicable to the contract unless they are expressly accepted in writing by the purchases.


For PRINCIPAL

Copy to:

1. Notice Board, GMC KLM/GMCH KLM
2. Website, GMC KLM

Sl No	Item Name	Specification	Quantity
1	Needle Burner with Syringe Destroyer –	Two slot easy operation for destroying Needle and Syringe – Needle burns electrically and syringe cuts manually – Can destroy disposable syringe needle 18 G to 28G – Collection receptacle to collect the waste – Provision ON/OFF switch with pilot lamp – Shock proof – main circuit breaker is provided – Portable compact, handy – High quality plastic material used for better finish – Power 100 Watts – Warranty 1 year	1
2	Sterilizer	Electrically operated with immersion heater – Made of high quality Stainless Steel (SS304) – Coil power minimum 1500w straight type – Material to be used 2.2 grade SS 20 gauge – Accurated dimension 24" x 12" x 12" – With Heat free handles for lid and base – For steam sterilization disinfection of surgical materials/instruments – Should be corrosion resistant and easy to clean – should provide high quality perforated instrument tray – Manual operated drain valve facility should be provided – Power source Single phase 220V/50hz 16A with 2m. 2.5sq.m. power cable with grade Bakelite and Ceramic kettle connector – Should bear ISI mark – Sample should be produced for selection	2
3	Vacuum Cleaner	<p>Suction of motor : 2000 mm/wc (19600 pascals) or more</p> <p>Power : 2000W or more</p> <p>Blower : 35 litres or above / sec</p> <p>Dust bag capacity : 8 litres or more</p> <p>Voltage : 230 V, 50 Hz single phase</p> <p>Noise : less than 88 db or less</p> <ul style="list-style-type: none"> • Should have the facility for Auto cord winder • Should have the provision in Wet and dry applications • Should be compatible for Deep cleaning in both indoor and outdoor applications • The system should have the Cartridge filter suitable for wet & dry use without filter replacement • Should collect the waste in the Paper filter bags • Should have an option to Switch wet & dry vacuum nozzle simultaneously • Should supplied heavy duty Brush with hard bristles • The Container capacity should be at least 5 ltr or more • The material of construction of the Container should be of high quality Plastic • Should have the Power cable length of at least 10 m with proper marking • Should supplied with a Suction hose of min 2 Meter length and 35 mm diameter 	1

		<ul style="list-style-type: none">Should supply with standard cartridge filterWarranty: One year. <p>ACCESSORIES TO BE SUPPLIED</p> <table><tr><td>Floor cum carpet brush</td><td>-</td><td>1 No</td></tr><tr><td>Corner cleaner</td><td>-</td><td>1 No</td></tr><tr><td>Surface cleaner</td><td>-</td><td>1 No</td></tr><tr><td>Small wet squeegee</td><td>-</td><td>1 No</td></tr><tr><td>Small wet crevice nozzle</td><td>-</td><td>1 No</td></tr><tr><td>Atomiser</td><td>-</td><td>1 No</td></tr><tr><td>Flexi cleaner</td><td>-</td><td>1 No</td></tr><tr><td>Hose pipe</td><td>-</td><td>1 No</td></tr><tr><td>Grill cleaner</td><td>-</td><td>1 No</td></tr><tr><td>Extension tubes</td><td>-</td><td>1+1 Each</td></tr><tr><td>Spray jar</td><td>-</td><td>1 No</td></tr><tr><td>Floor wet squeegee</td><td>-</td><td>1 No</td></tr><tr><td>Car wash adapter</td><td>-</td><td>1 No</td></tr></table>	Floor cum carpet brush	-	1 No	Corner cleaner	-	1 No	Surface cleaner	-	1 No	Small wet squeegee	-	1 No	Small wet crevice nozzle	-	1 No	Atomiser	-	1 No	Flexi cleaner	-	1 No	Hose pipe	-	1 No	Grill cleaner	-	1 No	Extension tubes	-	1+1 Each	Spray jar	-	1 No	Floor wet squeegee	-	1 No	Car wash adapter	-	1 No	
Floor cum carpet brush	-	1 No																																								
Corner cleaner	-	1 No																																								
Surface cleaner	-	1 No																																								
Small wet squeegee	-	1 No																																								
Small wet crevice nozzle	-	1 No																																								
Atomiser	-	1 No																																								
Flexi cleaner	-	1 No																																								
Hose pipe	-	1 No																																								
Grill cleaner	-	1 No																																								
Extension tubes	-	1+1 Each																																								
Spray jar	-	1 No																																								
Floor wet squeegee	-	1 No																																								
Car wash adapter	-	1 No																																								
4	Wall Clock	<ul style="list-style-type: none">Size of the dial should be of at least 16"Should be molded in ABS material CaseShould have Aluminum Brushed or Wood Finish paintingShould be operated on AA type BatteryShould have option to mount on Wall	3																																							
5	Electronic Kitchen Weighing Machine	<ul style="list-style-type: none">Accuracy : 100 gPlatter Size : 350 mm x 300 mm (Tolerance +/- 10%)The Electronic Weighing Scale should incorporate following features for user-friendly convenience.Display: LED / LCD : 5 digit.TARE facility with zero function.The Scale should have inbuilt rechargeable battery backup for minimum of 8 hrs.The Scale should be as per BIS specifications. The scale should have ISI mark.The equipment shall be supplied with valid stamping from Weight and Measures. The stamping shall be done free of cost during the warranty period and the CAMC rates offered shall include the stamping charges.The tenderer shall have valid sales and service license for Weighing Machines from Legal Metrology.	10																																							

6	Barometer Fotin	<p>This instrument should consists of Scale, Mercury-filled glass tube and Cistern. Scale should be graduated in hPa (mb) and mmHg on a brass tube marking apex of ivory pointer as cardinal point and should read by the vernier in 0.1 mm graduation,</p> <ul style="list-style-type: none"> Measuring method : Mercury column Measuring range : 870 to 1,090 hPa 650 to 820mmHg Min. graduation : 1hPa/1mmHg Vernier readings : 0.1hPa/0.1mmHg Accuracy : ± 0.5hPa Mounted Thermometer : Mercury-filled glass thermometer Measuring range : -20 to 50°C Min. graduation : 0.5°C Dimensions : 1,130 (H) x 100 (W) x 100 (D) mm Weight : Barometer: approx. 2.5 kg Mounting board: approx. 1.8 kg 	1
7	Chloroscope	<ul style="list-style-type: none"> Glass Wares : Glass Test Tubes - 2 Nos. Reagent : Orthotoludine (O.T.) Reagent - 15 ml. Colour Chart : Standard Residual Chlorine Colour Chart With Chart Holder Instruction Manual : Testing Procedure Carrying Case : Chlorine Tester Kit Box 	10
8	PORTABLE RECHARGEABLE SPEAKER WITH NECKBAND MICROPHONE	<ul style="list-style-type: none"> Power Output : 12W max Speaker Impedance : 4Ω Input Channel : mic-1;1.0mV,250mA Frequency Response : 80-12000Hz AC Adapter for charging : 1 No Built-in high capacity lithium ion battery Rechargeable lithium ion battery : 3.7 V,2000mAh Low battery LED indicator Neck band microphone element : Condenser, cardioids 	2

9	MULTIPURPOSE LASER POINTER	<ul style="list-style-type: none"> • Multifunctional touch-keys, built-in laser pointer for presentation for easy slideshow control. • Should have 2.4 GHz RF Wireless Technology and built-in USB receiver • Should have the following USB Presentation Clicker Buttons: <ul style="list-style-type: none"> ◦ Red laser / Equivalent ◦ page up (long press full screen/ Esc full screen) & page down (long press black screen/ Esc black screen) ◦ On/off switch. • Should have strong red laser pointer for presentation to easy to see against most backgrounds • The Laser pointer should have a range of minimum 20 foot wireless range for free to move around the room • Laser Class : Class 2 Laser. • Max Output : Less than 1mW. • Wave Length : 640nm (red light). • Battery life (Laser pointer) : Min. 15 Hour • Battery life (Presenter) : 1050-hour 	2
---	-------------------------------	--	---


For Principal