



GOVERNMENT MEDICAL COLLEGE

PARIPALLY, KOLLAM-691574

Telephone Office : 0474 2572574, Fax: 0474 2572579

Telephone Principal: 0474-2572572 Electronic mail: gmckollam@gmail.com

Section Email: acts.gmckollam@gmail.com

No. C1-E-798258/2023/GMC-KLM

Dated:21/12/2023

QUOTATION NOTICE

Quotation Number	C1/E-798258/2023/GMC-KLM Dated:21/12/2023
Due date and time for receipt of quotations	At 2.30 pm on- 11/01/2024
Date and time for opening of quotations	At 3.00 pm on 11/01/2024
Date up to which the rates are to remain firm for acceptance	31-03-2024
Designation and address of officer to whom the quotation is to be addressed	Principal Govt. Medical College, Kollam -691 574

Purchase of Air conditioner .(Pathology)

(Technical Specification Attached)

*** Rate should be quoted in the following format**

Sl. No	Name Item	Unit cost	% of GST & Rate	Unit.cost including GST	Qty.	Total cost Including GST

Sealed quotations are invited for the supply of the materials specified in the schedule attached below/overleaf. The rates quoted should be for delivery of the articles at the place mentioned below the schedule. The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted above. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for delivery of the articles should also be mentioned. Quotations not stipulating period of firmness and with price variation clause and/or 'subject to prior sale' condition are liable to be rejected.

The acceptance of the quotations will be subject to the following conditions:

1. Acceptance of the quotation constitutes a concluded contract. Nevertheless, the successful tenderer must within a fortnight/a month after the acceptance of his quotation furnish 5 per cent of the amount of the contract as security deposit and execute an agreement at his own cost for the satisfactory fulfillment of the contract, if so required.
2. Withdrawal from the quotation after it is accepted or failure to supply within a specified time or according to specifications will entail cancellation of the order and purchases being made at the offerers expenses from elsewhere, any loss incurred thereby being payable by the defaulting party. In such an event the Government reserves also the right to remove the defaulter's name from the list of Government suppliers permanently or for a specified number of years.
3. Samples, duly listed, should be forwarded if called for under separate cover and the unapproved samples got back as early as possible by the offerers at their own expenses and the Government will in no case be liable for any expenses on account of the value of the samples or their transport charges, etc. In case, the samples are sent by railway; the railway receipt should be sent separately,

- and not along with the quotation since the quotation will be opened only on the appointed day and demurrage will have to be paid if the railway parcels are not cleared in time. Quotations for the supply of materials are liable to be rejected unless samples, if called for of the materials tendered for are forwarded. The approved samples may or may not be returned at the discretion of the undersigned. Samples sent by V.P. Post or "freight to pay" will not be accepted.
4. No representation for enhancement of price once accepted will be considered during the currency of the contract.
 5. Any attempt on the part of tenderers or their agents to influence the Officers concerned in their favour by personal canvassing will disqualify the tenderers.
 6. If any license or permit is required, tenderers must specify in their quotation and also state the authority to whom application is to be made.
 7. The quotation may be for the entire or part supplies. But the tenderers should be prepared to carry out such portion of the supplies included in their quotation as may be allotted to them.
 8. (a) In cases where a successful tenderer, after having made partial supplies fails to fulfill the contracts in full, all or any of the materials not supplied may, at the discretion of the Purchasing Officer be purchased by means of another tender/quotation or by negotiation or from the next higher tenderer who had offered to supply already and the loss, if any, caused to the Government shall thereby together with such sums as may be fixed by the Government towards damages be recovered from the defaulting tenderer.
(b) Even in cases where no alternate purchases are arranged for the materials not supplied, the proportionate portion of the security deposit based on the cost of the materials not supplied at the rate shown in the tender of the defaulter shall be forfeited and balance alone shall be refunded.
(c) Any sum of money due and payable to the contractor (including Security Deposit returnable to him) under this contract may be appropriated by the Purchasing Officer or Government or any other person authorized by Government and set-off against any claim of the Purchasing Officer or Government for the payment of a sum of money arising out of or under any other contract made by the contractor with the Purchasing Officer or Government or any other person authorized by Government.
 9. The prices quoted should be inclusive of all taxes, duties, cesses, etc., which are or may become payable by the contractor under existing or future laws or rules of the country of origin/supply or delivery during the course of execution of the contract.
 10. (a) Ordinarily payments will be made only after the supplies are actually verified and taken to stock but in exceptional cases, payments against satisfactory shipping documents including certificates of Insurance will be made up to 90 per cent of the value of the materials at the discretion of Government. Bank charges incurred in connection with payment against documents through bank will be to the account of the contractor. The firms will produce stamped pre-receipted invoices in all cases where payments (advance/final) for release of railway receipts/shipping documents are made through Banks. In exceptional cases where the stamped receipts of the firms are not received for the payments (in advance) the unstamped receipt of the Bank (i.e. counterfoils of pay-in-slips issued by the Bank) alone may be accepted as a valid proof for the payment made.
(b) The tenderers shall quote also the percentage of rebate (discount) offered by them in case the payment is made promptly within fifteen days/within one month of taking delivery of stores.
 11. Any sum of money due and payable to the successful tenderer or contractor from Government shall be adjusted against any sum of money due to Government from him under any other contracts.
 12. Special conditions, if any, printed on the quotation sheets of the tenderer or attached with the tender will not be applicable to the contract unless they are expressly accepted in writing by the purchases.


For PRINCIPAL

Copy to:

1. Notice Board, GMC KLM/GMCH KLM
2. Website, GMC KLM

TECHNICAL SPECIFICATION

Air Conditioner 2 Ton

- Should be Split Inverter type Air Conditioner
- BEE Star Rating: 3 Star
- Cooling Capacity (KW/hr): above 6000 KW/hr
- Material of condenser coil: Copper
- Compressor Type:-Inverter/ Dual Inverter (Rotary/Scroll type)
- Compressor warranty: 5 years
- Air circulation (CFM H/M/L): above 500/450/350
- Moisture Removal (L/hr): above 1.8
- Refrigerant: - CFC Free R32/ R410A/ R132A
- IDU Noise level (dBA):55/50/45
- Control: Microprocessor controlled codeless remote
- Power Source (V/Hz/Ø): 230V /50Hz / single phase
- Display: LED/LCD
- Remote control distance: Min 10 meters

1. Voltage Stabilizer

- Wall mount type with Time delay, High & low voltage & Thermal overload protection.
- Capacity: 5 KVA
- Warranty: 2 years
- Input voltage: 170-220 V
- Output Voltage: 200-240 V
- High Voltage Cut Off: 240
- Efficiency: >95%
- Frequency: 50Hz

2. Items to be supplied along with:

- 16 mtr copper piping with super long insulation for suction line [One AC need 9 Meter and another one need 7 Meter]
- 16 mtr copper piping with super long insulation for Discharge line [One AC need 9 Meter and another one need 7 Meter]
- 16 mtr PVC piping for drain [One AC need 9 Meter and another one need 7 Meter]
- Electrical Connectivity
 - The Indoor – Outdoor unit shall be connected using three core 2.5 Sq mm power cable and adequate length required for connecting shall be supplied.
 - The input Power required for operations shall be connected from the adjacent power socket to the supplied Voltage Stabilizer. The stabiliser shall be connected to the system directly. All required length of cable as per site condition need to be delivered by the contractor itself.
- Base plate for hanging indoor unit



Pema

- Suitable 15/16 A 3 pin plug top of Indian Standard shall be provided

3. General Terms & Conditions

- All refrigerant pipe bends should be as gentle as possible. (Bending radius should be 30 to 40mm or larger)
- All Pipes must be restrained to the walls by proper saddles.
- The drain hose should point downward with an adequate slope for easy drain flow.
- In cases where the outdoor unit is installed below the indoor unit
 - Tape the piping, drain hose, and connecting cable from down to up.
 - Secure the tapped piping along the exterior wall using saddle or equivalent
- In cases where the Outdoor unit is installed above the Indoor unit
 - Tape the piping and connecting cable from down to up.
 - Secure the taped piping along the exterior wall. Form a trap to prevent water entering the room.
- Fix the piping onto the wall by saddle or equivalent.
- Separately wire power supply cord and connecting cable
- Use heat-proof electrical wiring (FRLS Wires 2.5 Sq mm/ 4 Sq mm) capable of withstanding temperature up to 75°C(167°F)
- Use outdoor and waterproof connection cable rated more than 300V for the connection between indoor and outdoor units. (Colour codes and standards of wiring as per KSEI shall be followed)

4. Installation of Indoor Unit – Location Selection.

- Ensure that the interval between a wall and the left (or right) of the unit is more than 10cm (3.9in). The unit should be installed as high as possible on the wall, allowing a minimum of 20cm (7.9in) from the ceiling
- Such a place where is permitting easy connection with the outdoor unit.
- Such a place where is 1 m or more away from other electrical appliances such as television, audio device, etc.
- Avoid a location where there is a heat source, high humidity or inflammable gas.
- Do not use the unit in the immediate surroundings of laundry, a bath, a shower or a swimming pool

5. Installation of outdoor Unit – Location Selection.

- Ensure that the space around the back and sides is more than 30cm (11.8in). The front of the unit should have more than 70cm (27.6in) of space
- The foundation must be solid enough to bear the weight and vibration unit.
- The space around the unit is adequate for ventilation.
- The location is not close to any flammable gases.
- The location is sufficiently isolated so that the running noise and the hot exhaust air do not disturb the user.
- Easy access to Service and Maintenance.

20.11.2023

20.12.23

Page 2 of 2
PRINCIPAL



Prerna N
Dr Prerna N
Prof & HOD
D. H. P. Patha